



SPECIFICATIONS	
CAPACITY (Nm)	300
OVERLOAD CAPACITY (%F.S.)	300
OUTPUT @ F.S. (mv/V)	2±0.2
POWER SUPPLY (V)	3.5-12
BRIDGE RESISTANCE (Ω) NOMINAL	700
NON-LINEARITY (%F.S.)	0.5
HYSTERESIS (%F.S.)	1.0
OPERATING TEMP. RANGE (°C)	-20 TO +85
CROSSTALK (%F.S.)	1.0
AXIAL FORCE FOR CROSSTALK (N)	200
RADIAL FORCE FOR CROSSTALK (N)	400
BENDING MOMENT FOR CROSSTALK (Nm)	50
TORSION ANGLE (CALCULATED)	0.04°
TORSIONAL STIFFNESS (KNm/RAD)	260
BENDING STIFFNESS (KNm/RAD)	25
MASS (Kg)	0.09

DRAWING IN THIRD ANGLE PROJECTION

WIRING CODE	
COLOR	FUNCTION
RED	+EX
GREEN	+SIG
BLACK	GND
WHITE	-SIG

SUNRISE INSTRUMENTS
www.srisensor.com

SINGLE AXIS TORQUE LOADCELL
 D62MM, 300 Nm

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MM	M2214H1	REV. A
---	---------	--------